



## AC2

### Description

The AC2 amplifier is a four-channel Class D amplifier with integrated DSP, specifically engineered to meet the demanding requirements of high-output fixed installations, touring, and rental companies. Designed for maximum flexibility in system design and production, it delivers exceptional performance and includes onboard DSP tailored for both current and future Plus Audio loudspeakers.

With seamless remote control and full system integration via NetControl software, the AC2 amplifier is an ideal choice for professionals who prioritize efficiency and reliability.

### Meta Fields

#### Features :

- Maximum output power 4x 1300/2300W @ 8%/4%

#### Specification :

Amplification class	Class D
Power supply model	Universal Switched Mode Power Supply (SMPS) with power 4 x 1300W RMS (at 8%)
Output power (RMS, 1% THD, 1kHz)	4 x 2300W RMS (at 4%)
Mains rating	100V - 240V ~ ± 10%, 50-60Hz
Nominal current requirements	16A for 200-240V
Nominal Signal Processor (DSP)	SHARC 32-bit, floating point, 96kHz sampling rate
Input / Output	4 analog input, 2 AES input, 4 output
Input delay	500 ms
Output delay	100ms
Preset	24
AD Dynamic range	122dBA
DA Dynamic range	123dBA
Input	Adjustable input level, Mute function
Output	10 bands IIR filter, FIR filter

Max Power Consumption	2500watt
Weight	12.3kg
Dimensions (HxWxD)	483x360x88mm