

MPS15A

Description

The Plus Audio MPS15A is an advanced multipurpose point source loudspeaker, crafted to deliver exceptional sound quality and durability for a variety of audio applications. Its injection-moulded cabinet is engineered to be 20% more rigid, offering enhanced strength and longevity.

Key Features:

- High Power Handling: Capable of delivering 4000W peak power, the MPS15A ensures powerful, clear audio output suitable for both large venues and demanding applications.
- Superior HF Performance: Features a high polymer diaphragm compression driver, which provides cleaner and more transparent high-frequency sound compared to conventional titanium diaphragm drivers.
- Versatile Connectivity: Includes Bluetooth with TWS for seamless wireless audio streaming, as well as 2 XLR balanced combo jacks for professional audio input. An XLR-M mix out facilitates easy system integration.
- Class D Amplification: Employs efficient, fanless Class D amplification, reducing noise while maintaining high performance. The system also includes 4-PEQ on the XLR channel for tailored sound control.
- User-Friendly Interface: Control and adjust settings via an intuitive Android and iOS app, and access detailed DSP features through a 2.4-inch color LCD screen. Features include ducking, system limiter, and a 170ms speaker delay for accurate time alignment.
- Flexible Mounting Options: The MPS15A offers a 90° x 70° coverage pattern and

includes a 35mm pole socket and three M10 suspension points for versatile rigging and mounting.

The MPS15A by Plus Audio represents a blend of cutting-edge technology and durable construction, designed to meet the needs of diverse audio applications with precision and reliability.

Meta Fields

Features:

- Components 1 x 15" LF driver, 1 x 1.35" comp driver
- SPLmax 131dB
- Dispersion 90° x 70°
- 2.4" Colour Display
- Weight 21.5kg

Specification:

Max. SPL	calculated	131dB
I'IUA. JI L	Calcalacca	10140

Frequency response 45 Hz - 20 kHz

Power amp output 1000W (RMS)

(peak power)

Amp type Class D

Low-/mid speaker 15"

HF driver 1.35"

Analog inputs 2x XLR combo balanced,

1x 3.5 mm stereo jack

Analog outputs 1x XLR balanced

Display 2.4" colour display

Output modes Mix out / Link Out

Bluetooth features Audio streaming and linking

Pole mount Compatible with standard

35mm mounting pole

Rigging points 3x M10

Power consumption 800W

Dimensions (WxHxD) $71.3 \times 43.0 \times 40.3 \text{ cm}$

Weight 21.5kg